

Modular Electronic Time Controls



FM1D20A



FM1D20E



FM2D50



0.1 lbs
0.05 kg
-14°F
(-40°C)
to
131°F
(68°C)

FM1D – A and E Series 24-hour and/or 7-Day

Wiring connections:

- "A" Models: screw terminals for #10 to #24 AWG wire
- "E" Models: 1/4 in. quick connects

Model #	Voltage	# of Circuits	Switch Rating	Programs	Mounting
FM1D20A-120	120 VAC	1	SPDT, 16 Amp	20	Surface/DIN Rail
FM1D20A-24	24 VAC/VDC	1	SPDT, 16 Amp	20	Surface/DIN Rail
FM1D20A-240	240 VAC	1	SPDT, 16 Amp	20	Surface/DIN Rail
FM1D20E-120	120 VAC	1	SPDT, 16 Amp	20	Flush
FM1D20E-24	24 VAC/VDC	1	SPDT, 16 Amp	20	Flush
FM1D20E-240	240 VAC	1	SPDT, 16 Amp	20	Flush
FM1D50A-12	12 VAC/VDC	1	SPDT, 16 Amp	50	Surface/DIN Rail
FM1D50A-120	120 VAC	1	SPDT, 16 Amp	50	Surface/DIN Rail
FM1D50A-24	24 VAC/VDC	1	SPDT, 16 Amp	50	Surface/DIN Rail
FM1D50A-240	240 VAC	1	SPDT, 16 Amp	50	Surface/DIN Rail
FM1D50E-12	12 VAC/VDC	1	SPDT, 16 Amp	50	Flush
FM1D50E-120	120 VAC	1	SPDT, 16 Amp	50	Flush
FM1D50E-24	24 VAC/VDC	1	SPDT, 16 Amp	50	Flush
FM1D50E-240	240 VAC	1	SPDT, 16 Amp	50	Flush

FM2D50 Series 24-hour and/or 7-day

Dual circuit timer allows for each circuit to be programmed separately or together

Model #	Volts AC	# of Circuits	Switch Rating	Programs	Mounting
FM2D50-120*	120	2	SPDT, 16 Amp	50	Flush or surface
FM2D50-24*	24	2	SPDT, 16 Amp	50	Flush or surface
FM2D50-240*	240	2	SPDT, 16 Amp	50	Flush or surface

* For DIN rail Mounting, order accessory, MB-DIN (DIN Rail Mounting Base).