


**NEW**




# Set in 3 Easy Steps



1) Set Time



2) Set Defrost



3) Set Defrost Duration

## G8000 Series Durable Mechanical Defrost Timer

- Long life welded silver contacts rated at 40 Amps, 2 HP rating
- Encapsulated time module design prevents dust and dirt buildup
- Heavy-duty synchronous motor
- Mechanism snaps into many existing enclosures and brackets
- Heavy-duty steel enclosure with knockouts on bottom, back, and sides
- Up to six defrost cycles per day
- Includes 4 trippers
- Defrost termination from 4 to 110 minutes in 2 minute increments
- Works with external temperature or pressure sensors
- Positive switch action side bar
- Quick and easy installation
- 2-year warranty



**Ratings:**  
**Electrical Ratings:** 40 A Resistive, 2 HP  
**Pilot Duty:** 1000VA  
**Enclosure:** Type 1 Indoor

Model #	Description	Input Voltage	Switch Type
G8045-00	Time Initiated. Time Terminated.	120 VAC, 60 Hz	1N.O./1N.C.
G8045-20	Time Initiated. Time Terminated.	208-240 VAC, 60 Hz	1N.O./1N.C.
G8145-00	Time Initiated. Temperature, Pressure or Time Terminated.	120 VAC, 60 Hz	1N.O./1N.C.
G8145-20	Time Initiated. Temperature, Pressure or Time Terminated.	208-240 VAC, 60 Hz	1N.O./1N.C.

For enclosure dimensions, see page 146

