http://waterheatertimer.org/Intermatic-Defrost-timers-and-manuals.html





GO!

Intermatic Incorporated 7777 Winn Road Spring Grove, IL 60081

Switch It Up! GRASSLIN INTERMATIC 24 HR DIAL TO SET DEFROST START TIME 01-1-0 PUSH POINTER AND ROTATE TO SET DEFROST \mathbb{C} **G8000 Series Defrost Timer** by INTERMATIC

Switch to the **G8000 Defrost Timer**

As a trusted industry leader in time-based controls for over 60 years, Intermatic proudly introduces the new **G8000 Defrost Timer**.

Complete with an industry-leading 2-year warranty, the G8000 features heavy-duty silver-plated welded amp contacts. Its encapsulated design prevents dust and dirt buildup.

The G8000 easily snaps into most enclosures, for quick and easy installation.

Why settle for less?

Switch to the most reliable name in mechanical controls with the Intermatic **G8000 Defrost Timer**



Standard Features

- 40 Amp 2 HP contacts
- Time Initiated. Temperature, Pressure, or Time Terminated.
- 1-6 defrost events per day
- Minimum Time Termination 4 min.
- Maximum Time Termination 110 min.
- Operating Voltage: 120 or 208-240 VAC, 60 Hz.
- Spare Tripper Holder


Get More... From Your Defrost Timer

	G8000	Competitors
2-year limited warranty	\checkmark	
Heavy-duty silver-plated welded 40 amp contacts	\checkmark	
Encapsulated timer module design prevents dust and dirt buildup	\checkmark	
Switching design exceeds 30,000 cycle UL873 Refrigeration standard	\checkmark	
Quick and easy installation	\checkmark	

Model #	VAC, 60 Hz	Switch	Description	
G8045-00	120	1 N.O./1 N.C.	Time Initiated.	
G8045-20	208-240	1 N.O./1 N.C.	Time Terminated.	
G8145-00	120	1 N.O./1 N.C.	Time Initiated.	
G8145-20	208-240	1 N.O./1 N.C.	Temperature, Pressure or Time Terminated.	

Pressure,

Gain Versatility... With the G8000 Timer Mechanism



Mechanism fits into most enclosures

Replaces the following

Intermatic	Paragon	SUPCO	Precision
G8045-00	8045-00	S804500	6045-00
G8045-20	8045-20	S804520	6045-20
G8145-00	8145-00	S814500	6145-00
G8145-20	8145-20	S814520	6145-20

