

Portable Outdoor Timers With GFCI & Photo Control

P1100 Series

Portable Outdoor Timers & Heavy-Duty Outdoor Timers

These portable outdoor timers are specially designed to control the filter pump of a portable pool or spa, but they can also be used to turn ON and OFF outdoor decorations, engine block heaters and other appliances, indoors or outdoors.

Applications:

- Filter Pumps
- Air Conditioners
- Signs
- Lights
- Engine Block Heaters
- Fans

Specifications:




Enclosure: Outdoor grade plastic

5 in. (12.7 cm) H x 5½ in. (13.97 cm) W x 3¾ in. (9.52 cm) D

Cord: 3 wire, outdoor grade, 22 in. long, with grounded plug

Timer: 24 hour with 23½ hour maximum ON time. Two ON, two OFF trippers: standard. Dial will accept up to 12 sets of trippers

Shipping Weight: 1.7 lbs (0.7 kg)

Model #	Description	Electrical	Plug & Receptacle
P1101	Timer	15 Amp (1800 W), Resistive or Tungsten; 1 HP Air Conditioner, (15 FLA, 90 LRA), Motor Load	5-15 
P1121	Timer	15 Amp (1800 W), Resistive or Tungsten; 1 HP Air Conditioner, (15 FLA, 90 LRA), Motor Load	5-15 
P1131	Heavy-Duty Timer w/Twist-Lock Plug & Receptacle	20 Amp Resistive, 1 HP, (15 FLA, 90 LRA) Motor Load	5L-20 

For additional trippers (2 ON 2 OFF per pack), order No. 156PB10398A.

P1200 Series

Two-Circuit Portable Outdoor Timer

These portable two-circuit above ground pool timers incorporate a plug in for a timed circuit (normally used for a pool pump) and a plug-in for a live circuit (typically used for a pool light). GFCI protected circuits and a three-prong grounded plug for the time switch supply are also built-in.

Applications:

- Above Ground Pool Pumps
- Above Ground Pool Lights

Specifications:



Enclosure: NEMA 3R rated for Indoor/Outdoor installation

9¾ in. (23.8 cm) H x 5½ in. (14.0 cm) W x 3¾ in. (9.2 cm) D

Knockouts: Combination ½ – ¾ in. nominal knockouts, one on the back and each side of enclosure, two pre-cut on bottom

Timer: 24 hour with 23½ hour maximum ON time. Two ON, two OFF trippers standard. Dial will accept up to 12 sets of trippers

Shipping Weight: 2.8 lbs. (1.3kg)

Model #	Description	Electrical	Plug & Receptacle
P1251P	PB913N84 Timer	15 Amp (1800 W), Resistive or Tungsten; 1 HP (15 FLA, 90 LRA) Motor Load w/photo control	5-15 
P1261P	PB913N84 Timer	15 Amp (1800 W), Resistive or Tungsten; 1 HP (15 FLA, 90 LRA) Motor Load	5-15 

For additional trippers (2 ON 2 OFF per pack), order No. 156PB10398A.

