

Time Switch Enclosures & Panels

D. 2-in-1 Raintight Enclosure and Panels

- **NEMA 3R Rated**
- Use where 2 time switches are to be mounted side by side
- Heavy-duty, spot-welded NEMA 3R construction with beige powder coat paint
- Hasp (with hole for lock) holds permanently attached hinged door closed
- Combination $\frac{1}{2}$ – $\frac{3}{4}$ in. nominal knockouts conveniently located – two on back, five on bottom and one on each side
- Top mounting brackets plus two holes below switch level on back of enclosure

Model Number	Description/ Enclosure or Panel – Size (H x W x D)	Weight
T10000R*	2-in-1 Indoor/Outdoor – 10½ in. x 10½ in. x 4 in.	6.5 lbs
(replaces 2T2089GA)	Enclosure	
T21000R*	Indoor/Outdoor Panel – 10½ in. x 10½ in. x 4 in. with 4/8 Breaker Base	
T30000R*	Indoor/Outdoor Panel – 16¾ in. x 10½ in. x 4¼ in. with 8/16 Breaker Base	11.0 lbs
T40000R*	Indoor/Outdoor Panel – 20¾ in. x 12¾ in. x 4¼ in. with 8/16 Breaker Base	17.0 lbs

* Available for SERIES T100, T170, T1900, T2000 and C8800. NOT FOR T1400/T1800 series and other models with carryover.

E. Flushmount Enclosure

- **NEMA 1 Rated**
- For concealing mechanism in wall and giving a finished, flush appearance
- Heavy-duty, formed steel construction with hinged door
- Gray finish with powder coat paint
- Convenient mounting holes
- Cutout 9⅞ in. H x 6 in. W x 4⅞ in. D; flange 11 in. H x 8 in. W

Model Number	Description	Weight
2T308A*	Standard Flushmount w/Lock	6.5 lbs
2T2365GA**	Flushmount Enclosure w/Lock	7.0 lbs
6ET1398GA	Flush Cover for ET70415CR and ET70415CR24	2.5 lbs

* Available for SERIES T100, T170, T180, T1900, T2000 and C8800. NOT FOR T1400/T1800/T1900 MODELS WITH BCR SUFFIX.

** Available for SERIES ET100C, ET170C, ET700C and models EH10, EH40, ET279C, ET7115C, ET7215C, ET70215C and ET70115C.

F. Mounting Brackets

- Heavy gauge steel mounting bracket mounts to a standard symmetrical rail TS35 according to DIN46277 and EN50022
- Ideal for panel mounting of mechanical or electronic time switch controls, alongside of other DIN rail mountable electrical devices
- Snap-in type bracket accepts a wide range of Intermatic time switches including most T100, T170, T180, T1900, T2000, C8800, ET100, ET170, ET700 and ET70000 time switches

Model Number	Description	Weight
22T535GR	DIN Rail Bracket – 6 x 5 x 2 in.	1.0 lbs
22T338GR	Surface Mount Snap-in Bracket – 6 x 5 x 2 in.	1.0 lbs



UL917 C22.2-177
E10694 LR3730

UL & CSA apply to all enclosures shown.