



Swimming Pool & Spa Controls and Control Centers

Pool/Spa Controls



T10404R

Model Number	Description/Mechanism	Switch	Clock Supply Volts 60 Hz.
T10000R	Enclosure Only	none	na
T10101R	Two T101M	SPST-SPST	120
T10004R	One T104M	none-DPST	208-240
T10404R	Two T104M	DPST-DPST	208-240
T10604R*	T106M & T104M	SPDT-DPST	208-240
T12404R	T104M201 & T104M	DPST-DPST	208-240

*For 2 Speed Pump Applications.
For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A.

Case 12" (30.5 cm) high x 12" (30.5 cm) wide x 4-1/4" (10.8 cm) deep, 0.048" steel with electrostatically applied light beige finish.

Knockouts Five combination 1/2" - 3/4" and two combination 3/4" - 1" knockouts on the bottom. One combination 1/2" - 3/4" on the left side and one combination 3/4" - 1" on the back. One knockout 1-3/4" x 2-3/4" on the right side for mounting switches or GFCI.

Time Switch Rating 40 Amp. resistive each pole 120-240 VAC, 40 Amp. tungsten, inductive or 1000 VA pilot duty each pole 120-240 VAC 2 H.P. (24 FLA) - 120 VAC; 5 H.P.(28 FLA) - 240 VAC.

Shipping Wt. 10 lbs. (4.5 kg) **Agency Approval** CSA/C-US

60 Amp Control Centers



T21004R

Model Number	Description/Mechanism	Switch	Clock Supply Volts 60 Hz.
T21000R	Enclosure Only	none	na
T21001R	T101M	SPST	120
T21004R	T104	DPST	208-240

For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A.

Case 16-3/4" (42.6 cm) high x 8-7/8" (22.5 cm) wide x 4-3/8" (11.1 cm) deep, 0.048" steel with electrostatically applied light beige finish.

Knockouts Five combination 1/2" - 3/4" and one 3/4" - 1" knockouts on the bottom. One combination 1/2" - 3/4" on the left side and one combination 3/4" - 1" on the back. One 1-3/4" x 2-3/4" knockout on the right side for mounting switches or GFCI.

Panel Rating 60 Amp. 120/240 Volt or 120/208 Volt; single phase-60 Hz.

Time Switch Rating 40 Amp. resistive each pole 120-240 VAC, 40 Amp. tungsten, inductive or 1000 VA pilot duty each pole 120-240 VAC 2 H.P.(24 FLA) - 120 VAC; 5 H.P.(28 FLA) - 240 VAC.

Shipping Wt. 12 lbs. (5.4 kg) **Agency Approval** CSA/C-US

100 Amp Control Centers



T32404R

Model Number	Description/Mechanism	Switch	Clock Supply Volts 60 Hz.
T30000R5	Enclosure Only	none	na
T30004R	One T104M	none-DPST	208-240
T30401R	T104M & T101M	DPST-SPST	240-120
T30404R	Two T104M	DPST-DPST	208-240
T32404R	T104M201 & T104M	DPST-DPST	208-240

For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A.

Case 16-1/2" (41.9 cm) high x 10-7/8" (27.6 cm) wide x 4-1/4" (10.8 cm) deep, 0.048" steel with electrostatically applied beige finish.

Knockouts Two 1/2", three combination 1/2" - 3/4", and two combination 3/4" - 1" knockouts on the bottom. One combination 3/4" - 1" on the left side. Four 1/2", three combination 1/2" - 3/4" on the back. One 1-3/4" x 2-3/4" knockout on the right side for mounting switches and GFCI.

Panel Rating 100 Amp. max., 120-240 VAC or 120-208 VAC; single phase.

Time Switch Rating 40 Amp. resistive each pole 120-240 VAC, 40 Amp. tungsten, inductive or 1000 VA pilot duty each pole 120-240 VAC 2 H.P. (24 FLA) - 120 VAC; 5 H.P.(28 FLA) - 240 VAC.

Shipping Wt. 18.60 lbs. (8.44 kg) **Agency Approval** CSA/C-US

125 Amp Control Centers



T40404R

Model Number	Description/Mechanism	Switch	Clock Supply Volts 60 Hz.
T40000R	Enclosure Only	none	na
T40000R4*	Enclosure w/ Inside Compartment	none	na
T40004R	One T104M	none-DPST	208-240
T40404R	Two T104M	DPST-DPST	208-240

*Enclosure only with inside wiring compartment for (2) wiring devices.
For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A.

Case 20-3/4" (52.7 cm) high x 12-3/4" (32.4 cm) wide x 4-1/4" (10.8 cm) deep, 0.048" steel with electrostatically applied beige finish.

Knockouts Seven combination 1/2" - 3/4", and three combination 3/4" - 1" knockouts on the bottom. Five combination 1/2" - 3/4", on the left side. One 1-3/4" x 2-3/4" knockout on the right side for mounting switches and GFCI.

Panel Rating 125 Amp. max. (Residential Service), 120-240 VAC or 120-208 VAC; single phase.

Time Switch Rating 40 Amp. resistive each pole 120-240 VAC, 40 Amp. tungsten, inductive or 1000 VA pilot duty each pole 120-240 VAC 2 H.P. (24 FLA) - 120 VAC; 5 H.P.(28 FLA) - 240 VAC.

Shipping Wt. 17 - 21 lbs. (7.7-9.5 kg) **Agency Approval** CSA/C-US

