

# Electromechanical Timer Modules

## KM2 Series

### 24 Hour, 7 Day

**APPLICATION:** The KM/2 series modules are designed to fit into tight locations. It offers up to 21A switching designed for control of heating, ventilating, air conditioning, refrigeration, lighting, security, circulating pumps, spas or any electrical load requiring 24-hour or 7-day scheduling.

### Specifications:

- Size:** 1.67" x 2.64" x 1.67"  
**Supply Voltage:** 24, 120, 240VAC  
**Power Consumption:** 1 VA  
**Switch Rating:** SPDT  
Resistive: 21A @ 250V  
Motor: 1HP @ 125VAC  
2HP @ 250VAC  
Inductive: 8A @ 250VAC  
Tungsten: 1350W

**Wiring Connections:** 1/4" quick-connects



### Features:

- Very small and compact, fits anywhere
- On/Auto/Off manual switch standard
- Captive trippers for easy programming
- 1/4" quick terminals

KM2 Series Ordering Data					
Grasslin/Intermatic Model	OPERATING FEATURES			Switch Output	
	Switch Program	Program On/Off Every	Minimum On/Off Time	Type	Rating
KM2STUH-120	24 Hr.	20 Minutes	20 Minutes	SPDT	21A Res.

