



For sales and support visit:
hubbellpowersystems.com/contact/

Home > Products > Lineman Grade Tools > Load Handling Equipment > Hoists - Mechanical > Epoxiglas® Hoist Link Sticks

Epoxiglas® Hoist Link Sticks

Epoxiglas® Hoist Link Sticks

To permit hot-line work with a nylon-strap ratchet hoist, a properly applied link stick insulates the hoist from an energized conductor. The hoist link stick is a 1-1/4"-diameter Epoxiglas pole with a steel hook on one end and a butt swivel on the other.

To apply the link stick, attach the hook of the stick to a wire grip using the hotstick eye to operate the hook. Complete the application by connecting the nylon-strap hoist to the link stick butt swivel and to a pole or crossarm.

Rated working load: 4,000 lb.



Catalog No.	Length between end fittings	Weight
C4001175	15" Epoxiglas	4 lb./1.8 kg.
C4002399	18" Epoxiglas	5 lb./2.25 kg.
C4002400	24" Epoxiglas	6 lb./2.7 kg.



All contents Copyright© 2001 - 2016 Hubbell Incorporated. All rights reserved. Because Hubbell has a policy of continuous product improvement, we reserve the right to change design specifications without notice.
[Terms of Use](#) | [Contact Us](#) | [Site Map](#) | [Careers](#)