




Standard Pulling Eyes

This inexpensive cost-cutter provides a large offset eye to accommodate three-ton chain hoist hooks, and leaves the anchor eye free with plenty of clearances for attaching formed wire grips. The E-95B Adapter Bushing quickly adjusts to fit 1/2", 5/8", 3/4", or 1" anchor rods. By removing the Adapter Bushing, the E-96 Pulling Eye fits 1 1/4" rods. The E-96 Pulling Eye is inexpensive and easy to use. One man can assemble and hook up in minutes. For working loads to approximately 6,000 lbs. (ultimate strength - 18,000 lbs).



Catalog Number	Weight
E-96	5 lb./272 kg

Crimping Tools

OH25 - Hytool

This dieless, full cycle ratchet tool provides one-hand operation. Installs service entrance splice connectors. Conductor range: #10 through 1/0.

5-Year Limited Warranty

The OH25 incorporates a full cycle ratchet and cam mechanism allowing an easy, one-hand crimping operation. The ratchet mechanism provides for properly completed crimps every time before the tool can be removed from the connection. The OH25 is designed to install 5/8" INDULICK AND LINKIT service entrance connectors with only (1) crimp per connector end, speeding installation time. The single crimp covers the complete contact area, eliminating possible overlapping or failure to make the proper number of crimps.



OUR840 - 840 Popper Hytool

For use on aluminum connectors from #8 AWG to 250 kcmil. **5-Year Limited Warranty.**

Max. Crimp force: 8,000 lbs.
Max. Handle Force: 8 lbs.



Crimping Tools

MD6-8 - Hytool

Hand operated tool. Installs full range of connectors (taps, splices, terminals): #14 through 4/0. Applications: Full Tension and Non-Tension.

The MD6-8 is designed to provide over 90,000 reliable crimps installing full-tension and non-tension connectors.



Y35 Hypress

The Y35 Hypress Tool incorporates a C-shaped, rotatable head for overhead line work and compression grounding applications. The hook style head with extensive ram travel provides for easy tapping and splicing of overhead lines as well as Hyground compression grounding systems. **5 Year Limited Warranty**



Y39 Hypress

The versatile, lightweight Y39 weighs 13 lbs., and its small 3-1/8" wide head rotates 180 degrees for convenience and flexibility. The tool provides 12 tons of crimping power, while its built-in overload valve automatically releases pressure when the crimp is completed.

The Y39 is designed for easy die insertion and removal without ball checks or set screws. Its rapid ram advance and trigger-controlled release eliminate unnecessary pumping after every crimp. **2 Year Limited Warranty**



Y750 & Y750-2 Rubber Covered Head

750 Revolver Hypress
Hydraulic Tool - 12 Ton Force
Hand-Operated

Conductor Range:
#12-750 KCMIL AL/CU
and #4-556.5 KCMIL



Crimping Tools

Y644M Dieless Hypress

The "1" Crimp - Range Taking
Hydraulic Tool
11 Ton Force
Hand Operated
#6-1000 KCMIL Copper Hylug Terminals
and Hylink Splices
#6-1000 KCMIL Aluminum Hylug Terminals
and Hylink Splices



Patriot PAT750-18V

Battery Actuated Tool
Hydraulic Self-Contained
12 Ton



Patriot PAT644-18V

Battery Actuated Tool
Hydraulic Self-Contained
11 Ton



Batool BCT500-HS

Battery Crimp Tool
Hydraulic Self Contained
6 Ton



BCC1000CUAL

Battery Actuated
Cable Cutter
The BCC1000CUAL is a 12-V-DC battery
actuated cable cutter capable of cutting up
to 750 kcmil hard drawn copper cable, and
up to 1000 kcmil soft drawn copper, and up
to 2" O.D. aluminum cable.
DO NOT CUT STEEL or ACSR.



Y60BHU & Y60BHU-D

60 Ton Remote Power Operated
The Y60BHU Hypress, single acting,
and Y60BHU-D Hypress, double
acting, are both designed to provide
fast, easy operation plus a durable
and substantially longer design life
expectancy. Both Y60BHU &
Y60BHU-D Hypress Tools accom-
modate the same "L" dies. The "L"
dies are designed for copper and
aluminum code cables and aerial
conductor sizes through 2500 kcmil
and will accommodate ACSR
through size 2156 (84/19) str. 5 Year Limited Warranty.



Y35BH Hypress

10,000 PSI
Remote Power Operated
Compression Tools.



Y39BH Hypress

10,000 PSI
Remote Power Operated
Compression Tool



Y750BH Hypress

10,000 PSI
12 Ton Battery Operated
Hydraulic Tool
Conductor Range:
#14-750 kcmil AL/CU
#4-556.5 kcmil ACSR



Y644MBH Dieless Hypress

10,000 PSI
Hydraulic Tool
Remote Operated



Y46 & Y46C Hypress

10,000 PSI
15 Ton Force
Remote Operated
Hydraulic Tool
The Y46 standard tool and
Y46C rubber covered tools are
lightweight, compact and
versatile with installation dies
for both circumferential and
nest-indentor types. Accessories include "U-" die adapter,
a cable cutting die for 1.2" diameter non-steel conductors,
plus a lifting eye and universal hot-stick adapter for
overhead line construction.
5 Year Limited Warranty



Y700DC-1B & Y420DC-1B

Battery Powered Hydraulic Pump
Hydraulic Output Pressures of:
10,000 PSI and 6,000 PSI





Crimping Tools

Electric/Hydraulic Pump EPP10 & EPP6

Both EPP10 and the EPP6 are equipped with a built-in, factory set pressure relief valve. An audible "pop" and recycling of the pump and relaxing of the hose, signals completion of the crimping./cutting cycle. Both pumps are supplied with a durable hand-held electric pendant switch, for remote operation of the unit, and have a manual selection switch mounted for operation of the unit at the pump. The operator can select which method is best suited for the application.

Hydraulic Output Pressure of: 10,000 PSI and 6,000 PSI.



Electric/Hydraulic Pump EP10, EP8, EP6, EP10-2, EP8-2, EP6-2

Electrically driven hydraulic pumps are supplied with a durable, hand-held electric pendent switch that remotely controls the pump and matches the output requirements of all Hypress remote heads and cutters. Each pump is equipped with a built-in factory set, pressure relief valve. An audible "pop" and recycling of the pump and relaxing of the hose, signals completion of the crimping/cutting cycle.

Hydraulic Output Pressures of:
10,000 PSI, 8,800 PSI, AND 6,000 PSI



Gasoline Engine Driven Hydraulic Pump GP10, GP8, GP6

The gasoline engine driven hydraulic pump is a heavy-duty design that is rugged and portable. Supplied with a four (4) H.P. engine, the pump operates all remote compression heads and cable cutters.

Each pump has a built-in, factory pre-set, automatic pressure release overload valve with a definite pulsing and recycling to signal the completion of a crimp. The manual control valve allows user to "Jog and Hold" due to the unique check valve design that keeps pressure in the output line until retracted.

Hydraulic Output Pressures of:
10,000 PSI, 8,800 PSI, AND 6,000 PSI



Nonconductive Hoses

PT29900-8

Length: 8'
Diameter: 3/16" or 1/4"
10,000 PSI
* With stackable couplers.

PT29900-10

Length: 10'
Diameter: 3/16" or 1/4"
10,000 PSI
* With stackable couplers.

PT29900-15

Length: 15'
Diameter: 3/16" or 1/4"
10,000 PSI
* With stackable couplers.

PT29900-25

Length: 25'
Diameter: 3/16" or 1/4"
10,000 PSI
* With stackable couplers.



6.2 Ton Flip-Top Dieless Crimping Tool VC6FT

- * Rapid Advance
- * Flip-Top Head Design
- * Eliminates the need for Dies
- * 6.2 Ton Output
- * External Pressure Adjustment
- * Carrying case is included.

Specifications:

Output: 6.2 Ton
Weight: 11.5 lbs.
Length: 23"
Jaw Opening: 1.5"
Connector Range: #10-750 MCM



**Please call us if you don't see what you
are looking for!**



1-800-247-5442

Crimping Tools

Type-O Tools



Descriptions for chart below:

- #1 / 17" Straight Handles/Non-Insulated Head
- #2 / 17" Straight Handles/Insulated Head
- #3 / 21" Straight Handles/Non-Insulated Head
- #4 / 21" Straight Handles/Insulated Head
- #5 / 17" Bent Handles/Non-Insulated Head
- #6 / 17" Bent Handles/Insulated Head

Catalog Numbers:

#	5/8" Fixed Nose Die*	"O" Fixed Nose Die*	620 Fixed Nose Die*	Fixed 5/8" & "D"	Fixed "O" & "D"
1	O-62F	O-63F	O-620F	O-65FB	O-68FB
2	O-62-3F	O-63-3F	O-620-3F	O-65-3FB	O-68-3FB
3	O-62-2-1F	O-63-2-1F	O-620-21-FB	O-65-21-FB	O-68-21-FB
4	O-62-2-2F	O-63-2-2F	O-620-22-FB	O-65-22-FB	O-68-22-FB
5	O-62-5-0F	O-63-5-0F	O-620-50-FB	O-65-50-FB	O-68-50-FB
6	O-62-5-3F	O-63-5-3F	O-620-53-FB	O-65-53-FB	O-68-53F

Visit Our Website!
www.Brenco-Inc.com

WE RENT CRIMPING TOOLS AND DIES!!

PLEASE CALL US FOR MORE
 INFORMATION!

WE ALSO REPAIR:

**MECHANICAL
 &
 HYDRAULIC CRIMPERS**

PUMPS

REMOTE HEADS

AND MANY OTHER ITEMS!

Please call us for any of your repair needs!



Crimping Dies



L-DIE



P-DIE



W-DIE



S-DIE



U-DIE



For 052&062 style tools



For WH2&WH3 Presses

**New & Used Dies are available for all
your crimping needs!**

Installation Tool	Corresponding Die Set
MD6	W-VT W-RT or X Die
Y29B	B-Nest Y29 Indentor
Y750 Y39 Y35	U-Die
Y45	S-Die
Y46	P-Die
Y48B	C-Nest Y48 Indentor
Y60BHU	L-Die

Die Identification Numbering System

U - TOOL TYPE (CHART I)

34 - WIRE SIZE (CHART II)

ART - (CHART III)

CHART I			
A - Y34A B - Y34BH C - Y48B	E - Y44B F - Y486RB G - Y34C L - Y60B	P - Y46 S - Y45 U - Y35 W-MD-6/OUR840	X - OUR840/MC-6
CHART II			
12 - #12 10 - #10 8c - #8 6C - #6 5C - #5	4C - #4 3C - #3 2C - #2 1C - #1 25 - 1/0	26 - 2/0 27 - 3/0 28 - 4/0 29 - 250 MCM 30 - 300 MCM	31 - 350 MCM 32 - 400 MCM 34 - 500 MCM 36 - 600 MCM 39 - 750 MCM 44 - 1000 MCM
CHART III			
A - ALUMINUM B - INDENTOR NEST (USED WITH INDENTOR DIE #Y34P**) R - ROUND DIE (CIRCUMFERENTIAL) T - TWIN DIE (BOTH HALVES)			

**ALSO AVAILABLE:
CUTTER DIES & DIE ADAPTERS**