

# Advanced Electronic Time Controls 1 & 2 Circuits



**Talento472-120plus**

**NEW PRODUCT**

## Talento 400 Plus 24-Hour/7-Day, Multi-Function Time Controls

The Talento 400 Plus series of electronic time switches provide 24-hour or 7-day control.



### Features:

- Offers automatic leap year and Daylight Saving Time adjustment once user enters current date and respective Daylight Saving Time change-over dates
- LCD display indicates load status, time of day, and week day
- In addition to the standard ON/OFF programming format, these units offer both pulse and cycle functions
- Pulse events are programmable to one or more seconds of duration
- Cycle function is programmable for both total cycle duration and ON duration in minutes or seconds
- Cycle function can be set to repeat indefinitely or to occur within a time and/or date range
- Programming is stored in non-volatile memory while a Lithium battery will keep the date and time for a minimum of 3 years
- Talento 400 plus comes in one or two circuits
- Two circuit models can be programmed for independent or simultaneous operation
- Manual override allows for Fixed ON or Fixed OFF operation
- Minimum ON Time: One second

### Applications:

- Billboards
- Automatic Shutters/Awnings
- Lighting Controls
- HVAC/R
- Pumps/Motors/Fans
- General Purpose Electrical Circuits

### Specifications:

| Model #             | Circuits | Volts AC | Switch Rating | Programs | Mounting †                 |
|---------------------|----------|----------|---------------|----------|----------------------------|
| Talento471-120plus* | 1        | 120      | SPDT, 16 Amp  | 50       | DIN Rail                   |
| Talento472-120plus* | 2        | 120      | SPDT, 16 Amp  | 50       | DIN Rail                   |
| GMX471-I-120plus    | 1        | 120      | SPDT, 16 Amp  | 50       | NEMA 1, Indoor enclosure   |
| GMX472-I-120plus    | 2        | 120      | SPDT, 16 Amp  | 50       | NEMA 1, Indoor enclosure   |
| GMX471-O-120plus    | 1        | 120      | SPDT, 16 Amp  | 50       | NEMA 3R, Outdoor enclosure |
| GMX472-O-120plus    | 2        | 120      | SPDT, 16 Amp  | 50       | NEMA 3R, Outdoor enclosure |

\* Mechanism only.

† See page 48 for enclosure options and details.



-13°F  
(-25°C)  
to  
131°F  
(55°C)