



:HHNO\ 'LJLWDO ,Q
% 1 ' 68 &

Function Description

- /DUJH /&' GLVSOD\
- \$0 30 FORFN GLVSOD\
-)RXU RSHUDWLQJ PRGHV 2)) 21 2)) \$872 21 \$872
- :LWK 1L 0+ UHFKDUJHDEOH EDWWHU\
- 3URJUDP XS WR 21 2))V GDLO\ 0LQ 6HWWLQJ PLQXWH 0D[6H
- :LWK GD\OLJKW VDYLQJ WLPH IXQFWLRQ
- :LWK ZD\ FRQWURO IXQFWLRQ
- 2SHUDWLQJ HQYLURQPHQW IRU LQGRRU XVH RQO\
- 2SHUDWLQJ 7HPSHUDWXUH WZ¥ WR ž)
- 6WRUDJH 7HPSHUDWXUH WZ¥ WR ž)

Input & Output Appearance

&RQQHFW WR IL[HG ZLULQJ

Ratings & Approval

Voltage Compatibility: 5VAC
 Frequency: 60Hz
 Max. Load\$: 5HVLVWLYH
 \$: 7XQJVWHQ
 \$: (OHFWURQRQDQVW
 2WKHSDWLQJ43 79

Packing

Product Measurement (inches):
 Product Weight (ounce):
 Unit Package Measurements (inches):
 Unit Package Weight (ounce):
 Master Carton Measurements (inches):
 Master Carton Weight (lbs):
 Master Carton Quantity: 50PCS
 Master Carton Cube (cu.ft): 1.