



Kenmore 38 Gallon Short Power Miser 6 Electric Water Heater

42-32626

- Factory-installed temperature and pressure safety valve
- Limeguard elements resist lime build-up and lasts longer than standard elements
- DualWatt lower element easily converts from 3,800 to 5,500 Watt operation to fit the customer's wiring
- Cobalt Blue Ultra Coat Glass-Lined tank with single anode rod for tank protection
- Energy efficient foam insulation
- Roto-Swirl self-cleaning cold water inlet tube

Selection	42-32626
Features	
Tank Capacity	38 Gallons
Number of Elements per Unit	2
Upper Element Type	Limeguard
Lower Element Type	Limeguard DualWatt
Anode	1
Dip Tube	PEX Roto-Swirl
Tank Material	Glass-Lined Steel
Insulation Material	Foam
Insulation R Value	16
Insulation Depth (Inches)	2
Recovery at 90 Degree Rise	17.3 G.P.H. @ 3,800W 25 G.P.H. @ 5,500W
First Hour Rating	45 Gallons @ 3,800W 47 Gallons @ 5,500W
Voltage	240 Volts
Kilowatt Hrs. Per Year	4,773
Wattage at 240V	5,500 Watts
Maximum Fuse Required	30 Amps
Minimum Wire Size	10 Gauge
Alternate Dual Power	
Wattage at 240V	3,800 Watts
Maximum Fuse Required	20 Amps
Minimum Wire Size	12 Gauge
Est. Yearly Operating Cost	\$508
Shipping Weight (Approx. Lbs.)	120
Dimensions (Inches)	
Maximum Height	32.25
Height	31.5
Width	23
Depth	23
Diameter	23
Warranty	
1-Year Limited Warranty – Entire Appliance	Labor
6-Year Limited Warranty	Tank & Parts

If used for other than private family purposes, warranty applies for only 2 years.