

# SS SERIES

## AUTO OFF IN-WALL TIME SWITCH



### SPECIFICATIONS

**TIMING ACCURACY:**  
±5% @ 60° to 80°F.

**INPUT VOLTAGE:**  
24/120/208-240/277VAC, 50/60Hz.

**WIRE SIZE:** #18AWG.

**OPERATING TEMPERATURE:**  
0°F to +100°F (-17°C to +37°C).

### APPLICATIONS



- Bathroom fans and lights
- Indoor/Outdoor lighting
- Storage areas
- Hospitality areas

# D SERIES

## ELECTRONIC AUTO OFF IN-WALL TIME SWITCH



### SPECIFICATIONS

**TIMING ACCURACY:** Line voltage.

**INPUT VOLTAGE:** 120VAC, 60Hz.

**WIRE SIZE:** #14AWG.

**OPERATING TEMPERATURE:**  
32°F to 122°F (0°C to 50°C).

### APPLICATIONS



- Whole house fans
- Indoor/Outdoor lighting
- Bathroom fans and lights
- Self storage

### FEATURES

**VARIABLE TIMING:** Choose from 1 minute to 18 hours.

**FLASH WARNING:** "F" suffix models with flicker feature turns load off for 1/2 second, 2 minutes before end of timed cycle and again 1 minute before end of timed cycle.

**AUDIBLE WARNING:** "B" suffix model will buzz that every 12 seconds during the last 2 minutes of timed cycle.

**TAMPER RESISTANT:** Time ON interval preset is hidden behind wall plate.

**EASY SET:** Small screw driver adjustment provides quick set-up of timing.

**EASY WIRING:** No neutral needed, great for retrofit.

**3-WAY:** SS13 SERIES replaces standard 3-way switch with no re-wiring.

**COLOR:** White.

### ORDERING INFO

CATALOG NO.	UPC CODE	INPUT SUPPLY (VAC) 50/60Hz	WARNING BEFORE TIME OUT	SWITCH TYPE
SS20	14005	24/120/208-240/277	None	Single pole
SS20F	14008	24/120/208-240/277	*Flicker	Single pole
SS13F	14007	24/120/208-240/277	*Flicker	3-way
SS13B	14006	24/120/208-240/277	**Beep	3-way

\*Flicker feature turns load OFF for 1/2 second, 2 minutes before end of timed cycle and again 1 minute before end of timed cycle.

\*\*Beep feature will begin a 1/2 second audible warning every 12 seconds during the last 2 minutes of timed cycle.

### CONTACT RATINGS

TYPE	CONTACT RATINGS	MINIMUM LOAD	
		VOLTS	WATTS
SS13F & SS13B	.25-4.0A Resistive	24	6
	.25-4.0A Ballast*	120	30
	.25-4.0A Tungsten	208	50
	1/8HP @ 120VAC	240	60
	1/3HP @ 240VAC	277	70
SS20 & SS20F	.50-7.25A Resistive	24	12
	.50-7.25A Ballast*	120	60
	.50-4.0A Tungsten	208	105
	1/8HP @ 120VAC	240	120
	1/2HP @ 204VAC	277	150

\*Not compatible with compact fluorescent lamps (CFL) and electronic fluorescent ballasts.

### FEATURES

**VARIABLE TIMING:** Button push changes time ON setting.  
**D1060M:** 10, 20, 30, 60 minute.  
**D212H:** 2, 4, 8, 12 hour.

**LED DISPLAY:** Indicator moves to new range as timer counts down.

**TAMPER RESISTANT:** Time ON interval preset.

**EASY SET:** No adjustments, just wire and go!

**WIRING:** Requires a neutral.

**THREE COLORS:** Ivory, Light Almond, White.

### ORDERING INFO

CATALOG NO.	UPC CODE	INPUT SUPPLY (VAC) 60Hz	TIME SETTINGS	OUTPUT CONTACTS
D212H	14021	120	Ivory	2, 4, 8, 12 HOURS
D212HA	14022	120	Light Almond	2, 4, 8, 12 HOURS
D212HW	14023	120	White	2, 4, 8, 12 HOURS
D1060M	14025	120	Ivory	10, 20, 30, 60 MINUTES
D1060LA	14024	120	Light Almond	10, 20, 30, 60 MINUTES
D1060MW	14025	120	White	10, 20, 30, 60 MINUTES

### CONTACT RATINGS

TYPE	VOLTAGE	RATING
General Purpose	120VAC	15A
Resistive	120VAC	1000W
Tungsten	120VAC	1000W
Motor	120VAC	1/4HP