

# SS SERIES

## AUTO OFF IN-WALL TIME SWITCH



### SPECIFICATIONS

**TIMING ACCURACY:**  
±5% @ 60° to 80°F.

**INPUT VOLTAGE:**  
24/120/208-240/277VAC, 50/60Hz.

**WIRE SIZE:** #18AWG.

**OPERATING TEMPERATURE:**  
0°F to +100°F (-17°C to +37°C).

### APPLICATIONS



- Bathroom fans and lights
- Indoor/Outdoor lighting
- Storage areas
- Hospitality areas

# D SERIES

## ELECTRONIC AUTO OFF IN-WALL TIME SWITCH



### SPECIFICATIONS

**TIMING ACCURACY:** Line voltage.

**INPUT VOLTAGE:** 120VAC, 60Hz.

**WIRE SIZE:** #14AWG.

**OPERATING TEMPERATURE:**  
32°F to 122°F (0°C to 50°C).

### APPLICATIONS



- Whole house fans
- Indoor/Outdoor lighting
- Bathroom fans and lights
- Self storage

### FEATURES

**VARIABLE TIMING:** Choose from 1 minute to 18 hours.

**FLASH WARNING:** "F" suffix models with flicker feature turns load off for 1/2 second, 2 minutes before end of timed cycle and again 1 minute before end of timed cycle.

**AUDIBLE WARNING:** "B" suffix model will buzz that every 12 seconds during the last 2 minutes of timed cycle.

**TAMPER RESISTANT:** Time ON interval preset is hidden behind wall plate.

**EASY SET:** Small screw driver adjustment provides quick set-up of timing.

**EASY WIRING:** No neutral needed, great for retrofit.

**3-WAY:** SS13 SERIES replaces standard 3-way switch with no re-wiring.

**COLOR:** White.

### ORDERING INFO

| CATALOG NO. | UPC CODE | INPUT SUPPLY (VAC) 50/60Hz | WARNING BEFORE TIME OUT | SWITCH TYPE |
|-------------|----------|----------------------------|-------------------------|-------------|
| SS20        | 14005    | 24/120/208-240/277         | None                    | Single pole |
| SS20F       | 14008    | 24/120/208-240/277         | *Flicker                | Single pole |
| SS13F       | 14007    | 24/120/208-240/277         | *Flicker                | 3-way       |
| SS13B       | 14006    | 24/120/208-240/277         | **Beep                  | 3-way       |

\*Flicker feature turns load OFF for 1/2 second, 2 minutes before end of timed cycle and again 1 minute before end of timed cycle.

\*\*Beep feature will begin a 1/2 second audible warning every 12 seconds during the last 2 minutes of timed cycle.

### CONTACT RATINGS

| TYPE          | CONTACT RATINGS     | MINIMUM LOAD |       |
|---------------|---------------------|--------------|-------|
|               |                     | VOLTS        | WATTS |
| SS13F & SS13B | .25-4.0A Resistive  | 24           | 6     |
|               | .25-4.0A Ballast*   | 120          | 30    |
|               | .25-4.0A Tungsten   | 208          | 50    |
|               | 1/8HP @ 120VAC      | 240          | 60    |
|               | 1/3HP @ 240VAC      | 277          | 70    |
| SS20 & SS20F  | .50-7.25A Resistive | 24           | 12    |
|               | .50-7.25A Ballast*  | 120          | 60    |
|               | .50-4.0A Tungsten   | 208          | 105   |
|               | 1/8HP @ 120VAC      | 240          | 120   |
|               | 1/2HP @ 204VAC      | 277          | 150   |

\*Not compatible with compact fluorescent lamps (CFL) and electronic fluorescent ballasts.

### FEATURES

**VARIABLE TIMING:** Button push changes time ON setting.  
**D1060M:** 10, 20, 30, 60 minute.  
**D212H:** 2, 4, 8, 12 hour.

**LED DISPLAY:** Indicator moves to new range as timer counts down.

**TAMPER RESISTANT:** Time ON interval preset.

**EASY SET:** No adjustments, just wire and go!

**WIRING:** Requires a neutral.

**THREE COLORS:** Ivory, Light Almond, White.

### ORDERING INFO

| CATALOG NO. | UPC CODE | INPUT SUPPLY (VAC) 60Hz | TIME SETTINGS | OUTPUT CONTACTS        |
|-------------|----------|-------------------------|---------------|------------------------|
| D212H       | 14021    | 120                     | Ivory         | 2, 4, 8, 12 HOURS      |
| D212HA      | 14022    | 120                     | Light Almond  | 2, 4, 8, 12 HOURS      |
| D212HW      | 14023    | 120                     | White         | 2, 4, 8, 12 HOURS      |
| D1060M      | 14025    | 120                     | Ivory         | 10, 20, 30, 60 MINUTES |
| D1060LA     | 14024    | 120                     | Light Almond  | 10, 20, 30, 60 MINUTES |
| D1060MW     | 14025    | 120                     | White         | 10, 20, 30, 60 MINUTES |

### CONTACT RATINGS

| TYPE            | VOLTAGE | RATING |
|-----------------|---------|--------|
| General Purpose | 120VAC  | 15A    |
| Resistive       | 120VAC  | 1000W  |
| Tungsten        | 120VAC  | 1000W  |
| Motor           | 120VAC  | 1/4HP  |